PRODUCT - INFORMATION





Perfluorinated Solvent and Cleaner

Product description

CARBAFLO® 790 is a FCKW free, non flammable Fluid without any Ozone hazardous potential, which is ideal as thinner for all CARBAFLO® - Lubricants for a finer application but also as a cleaner for use prior to the application of the lubricant.

Ingredients

CARBAFLO® is based on low viscosity Perflouroalkylether.

TEST	SPECIFICATION	RESULT
Appearance Colour Specific gravity (20°C) Ph Boil point Melting point Flame point Vapour pressure Viscosity Evaporation rate (lb / hr - ft²) Water solubility (20°C) Surface tension (20°C)	ISO 3679	fluid transparent 1,6 g/cm³ Neutral 79°C at 25°C: 165 torr 0,75 cSt 126 +/-33 mg/l 14 ppm (vt)

Advantage

CARBAFLO® 790 is used for cleaning of highly sensible equipment as:

- Oxygen equipment
- **Navigation instruments**
- Vacuum pumps
- Components lubricated with any CARBAFLO® Products
- electronic devices
- Computer hard drives and floppy- / CD drives
- Mirrors, lenses and laser heads
- Analytic equipment
- Medical devices

Application

Parts are cleaned with CARBAFLO® 790 through dipping or with brush or cloth.



FUCHS LUBRITECH GMBH

